

Name	WAX PRESTIGIO ANTICO CERA PER STUCCO VENEZIANO
Description	Protective wax for floated and stucco finishes
Main Features	Balanced blend of natural virgin waxes, in suspension in a solvent.
Baldini Tecnicolor	
Classification (UNI 8681)	
Application Cycle	Can be applied using a rag, pad, or plastering trowel. Only a single very thin coat need be applied. When it is properly dry buff up using a soft cloth, or orbital polisher operating at low rpm. Do not apply Cera per Stucco Veneziano on surfaces that are still damp.
Practical Advice	In summer this product may become too fluid. It is best to allow it to congeal in a cool place and to mix it again. Air rooms during application and before inhabiting them overnight. Clean tools used with solvent immediately after use. Ambient and surface conditions: Ambient Temperature : min 5°C / max 35; Ambient Relative Humidity: Can be applied in very damp settings. Surface Temperature : min. 5°C / max 35; Dry Surface.
Safety data	<ul style="list-style-type: none">• Keep the tin tightly closed, upside down and protected from frost.• Labelling required.• User information is contained in the relevant safety sheet.• Empty containers and containers with traces of dried product film must be disposed of according to local regulations.
Tender item	Application of PRESTIGIO ANTICO CERA PER STUCCO VENEZIANO with an average consumption of _____ l per sq. m, to be applied in two coats at a cost of € _____ per sq. m, including materials and labour and excluding scaffoldings and surface dressing.

Atova International

2452 N. Harlem Ave.
Elmwood Park, IL 60707
Phone: 1-866-452-9982
Fax: 1-708-452-8331
www.paintandplasters.com
techsupport@paintandplasters.com

